

PRODUCT HEALTH AND SAFETY DATA SHEET. LIME BASE STONE REPAIR PREMIX

PRODUCT

Contains sand, stone-dust and lime.

USAGE

Add water to achieve required consistency.

POTENTIAL HAZARDS

When dry this product should be handled as abrasive and alkaline When mixed with water this product has an abrasive alkaline nature.

Wet or dry this material can cause injury to the eyes.

Contact with wet cement can cause adverse reactions to skin.

- 1. Eyes are vulnerable and damage will increase with contact time.
- 2. Irritant contact dermatitis can be caused by the alkaline and abrasive wet mixture.
- 3. Lime burn may occur as a result of contact when newly mixed with water.

PROTECTION

Direct contact should be avoided. Use waterproof clothing.

FIRST AID

- 1) After eye contact wash eyes with clean water for 15 minutes. Seek medical advice without delay.
- 2) Contact with the material must be washed off quickly with water. Seek medical advice if adverse symptoms persist.
- 3) Clothing contaminated by wet mortar should be removed and washed before further use.
- 4) If the material is ingested do not induce vomiting. Wash out mouth with water and drink plenty of water.

STORAGE

Material should be stored in dry conditions.

SPILLAGE

In the event of spillage drainage to watercourses should be avoided.

DISPOSAL

Hardened material is inert, unmixed dry material should be disposed of at a tip authorised to accept builders' waste.

ROWLAND PREMIX LIMITED THE STONE YARD, CLANAGE ROAD, BRISTOL BS3 2JX. TELEPHONE: 0117 953 3550

FACSIMILE: 0117 953 3552 www.rowlandpremix.co.uk